

# SAFETY DATA SHEET

## KLINGERtop-chem-2006

Page 1 of 6

### 1 - IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name** KLINGERtop-chem-2006

**Other Names** PTFE Sheeting/Jointing/Gaskets KLINGERtop-chem-2006

**Recommended Use** High temperature gasket material

**Supplier** KLINGER Limited (ABN 95 008 679 838)  
38 McDowell St  
Welshpool  
WA 6106  
AUSTRALIA  
Tel +61 (0)8 9251 1600 or 1300 798 279  
(0800 – 1700 Australian Western Standard Time – GMT +8 hrs)  
Fax +61 (0)8 9350 9286

**Emergency Telephone Number:** +61 412626004

### 2 - HAZARDS IDENTIFICATION

Not classified as hazardous according to the criteria of **Safe Work Australia** and **GHS (Globally Harmonized System of Classification and Labelling of Chemicals)**.

**Classification according to GHS:** Not Classified

**GHS Label Elements:** Not Applicable for these products.

**Other Hazard Information:** The product is considered harmless to health and the environment in the form supplied and if stored and handled in the correct manner – see Section 7. No hazards are known based on present information.

### 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS	Proportion
PTFE (Polytetrafluoroethylene)	9002-84-0	>60%
Barium Sulfate	13462-86-7	<10%

#### **4 - FIRST AID MEASURES**

<b>Inhalation</b>	Dust arising from working the product should be treated as nuisance particulate material. Inhalation of dust may cause irritation to the mucous membranes and upper respiratory tract. Movement of exposed individual to fresh air is recommended. When material is heated to above 300°C thermal decomposition begins to occur. Thermal decomposition products of fluorinated products may cause polymer fume fever with flu-like symptoms which subside within 36 to 48 hours
<b>Skin</b>	Generation of dust may cause mechanical abrasion. Wash skin with soap and water. Launder heavily contaminated clothing before reuse. Seek medical advice if irritation develops.
<b>Eye</b>	May cause mechanical irritation in contact with eyes. Remove small solid particles and rinse with water for a minimum of 15 minutes. In all cases of eye contamination, it is a sensible precaution to seek medical advice.
<b>Ingestion</b>	Not hazardous. Not a likely source of exposure. If ingested, give plenty of fluid to assist passage through system. Seek medical attention if irritation occurs.

#### **5 - FIRE FIGHTING MEASURES**

<b>Suitable Extinguishing Media</b>	Water, carbon dioxide, powder extinguishers, foam extinguishers
<b>Hazards from Combustion Products</b>	Fluorinated olefins, Carbonyl fluoride, Hydrogen Fluoride. At temperatures exceeding 400°C the quantity of pyrolysis product increases rapidly and so does their toxic nature. Small amounts of octafluoroisobutylene have been identified.
<b>Precautions for Firefighters and Special Protective Equipment</b>	Breathing apparatus and eye protection must be worn to protect from dust and fumes.

#### **6 - ACCIDENTAL RELEASE MEASURES**

**Emergency Procedures**                      Fire: See Section 5

# SAFETY DATA SHEET

## KLINGER<sup>top</sup>-chem-2006

Page 3 of 6

Personal: See Section 4  
Environmental: No known environmental hazards exist.

### Methods and Materials for Containment and Cleanup

Approved vacuum cleaners with high efficiency filters (HEPA) conforming to AS3544 or equivalent must be used to clean areas. Spills which involve powder, dusts or granules may create a slip hazard and should be cleaned up immediately. Sweep up but avoid generating dusts.

### Additional

In the case of improper use (see Section 8) fine dust may result. Adequate suction and filtering of the exhaust air should be ensured.

## 7 - HANDLING AND STORAGE

### Handling

No special precautions necessary when handling the material in its finished form. However, whenever further processing of the product is undertaken, potential for the generation of dust exists. See Section 8.

### Storage

Store in a cool, dry, well ventilated area removed from foodstuffs. Material is only flammable through the effects of intensive heat. Excessive heat in the storage area may diminish the product's performance in its intended application.

## 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

### National Exposure Standards (Time-Weighted Averages)

PTFE Dust 10mg/m<sup>3</sup> ES-TWA  
(Recommended - Note that PTFE has no current assigned exposure standard, however as a general safety precaution the above guideline may be used.)  
Barium Sulfate: 5mg/m<sup>3</sup> TWA/PEL (Respirable fraction)

### Biological Limit Value

No Biological Limit Value allocated.

### Engineering Controls

Ensure adequate ventilation exists to maintain air concentrations below exposure standards. Do not inhale dust. Use localised extraction or wet methods of work to control dust levels.

# SAFETY DATA SHEET

## KLINGERtop-chem-2006

Page 4 of 6

**Personal Protective Equipment** No special precautions necessary when handling the material in its finished form. However, whenever further processing of gaskets is undertaken, the potential for the release of particulates that may cause mechanical abrasion exists. In the case of particle generation exceeding the above-noted National Exposure Standards, recommended PPE are rubber/PVC gloves, coveralls, safety glasses and a P2 particulate (AS1716 or equivalent) respirator. When removing embrittled or spent material or when high levels of dust exist a full-face class H particulate cartridge respirator or full-face positive pressure demand airline respirator (AS1716 or equivalent) is recommended. Good hygiene practices must always be maintained.

### 9 - PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	Form: Sheets or cut gaskets Colour: White
<b>Odour</b>	None
<b>pH</b>	Not applicable
<b>Vapour Pressure</b>	Not applicable
<b>Vapour Density</b>	Not applicable
<b>Boiling Point/Range</b>	Not applicable
<b>Freezing/Melting Point</b>	Not applicable
<b>Flashpoint</b>	Not-flammable
<b>Solubility (water)</b>	Insoluble
<b>Specific Gravity/Density</b>	3.0 g/cm <sup>3</sup>
<b>Auto Ignition Temperature:</b>	Not self-igniting
<b>Additional:</b>	None

## **10 - STABILITY AND REACTIVITY**

**Chemical stability** Stable under intended operating conditions.

**Conditions to Avoid** Not known

**Incompatible Materials** Not known

### **Hazardous Decomposition**

**Products** When material is heated to above 300°C thermal decomposition begins to occur. Thermal decomposition products of fluorinated products may cause polymer fume fever with flu-like symptoms which subside within 36 to 48 hours.

## **11 - TOXICOLOGICAL INFORMATION**

In case of the intended use no toxicological effects are known.

The most common source of exposure is experienced when smoking cigarettes contaminated with PTFE dust.

No toxicity was observed in male/female rats when fed PTFE (up to 25%) for a period of 90 days.

Rats were implanted with PTFE. Local sarcomas were induced during this testing procedure, however this is not considered relevant under normal industrial usage.

The agent is not classifiable as to its carcinogenicity to humans.

## **12 - ECOLOGICAL INFORMATION**

**Ecotoxicity** Not known. Insoluble in water, precipitates. Although inert as a finished product, avoid contamination of drains or waterways to prevent accumulation in the aquatic environment.

**Persistence and Degradability** Not known. Not biologically degradable (self-classification).

**Mobility** Not known

## **13 - DISPOSAL CONSIDERATIONS**

**Disposal Methods** No special requirements exist. This is a thermoplastic material hence recycling is preferable to landfill disposal. Do not dispose of in an incineration system under any circumstance. Local, state and federal statutory regulations must be observed

**Special Precautions**            Not applicable

**14 - TRANSPORT INFORMATION**

**UN Number**                    None allocated

**UN Proper Shipping Name**    None allocated

**Class and Subsidiary Risks**    Not relevant

**Packing Group**                Not relevant

**Special Precautions for User**    Do not transport with Explosives, Oxidising agents, Organic peroxides and foodstuffs. In sheet and cut gasket form there is no risk associated with the product under normal transport conditions. Not defined as a Dangerous Good by the Australian Code for the Transport of Dangerous Goods by Road and Rail.

**Hazchem Code**                None allocated

**15 - REGULATORY INFORMATION**

Regulations for dangerous materials not applicable.

**16 - OTHER INFORMATION**

**Date of issue/revision:**        05.03.25

All information and recommendations contained in this publication are based on the present level of knowledge and experience. Since the conditions of use are beyond our control, users must satisfy themselves that products are suitable for the intended processes and applications. No warranty is given or implied in respect of information and recommendations or that any use of the products will not infringe rights belonging to other parties. Our most current General Sales Conditions shall apply.

**END OF MSDS**